

Alco

Non-Removable Cast Resin

FEATURES:

Features	<p>Suitable for low voltage plastic or paper insulated cables rated up to 1kV, and telecommunications and signal plastic or paper insulated cables</p> <p>Suitable for mechanical protection and water-sealing on medium voltage cables</p> <p>Halogen-free, unfilled two-component polyurethane (PUR) cast-resin</p> <p>Specially developed for cable joints</p> <p>Non-toxic emission during mixing and casting</p> <p>Excellent hydrolytic resistance</p> <p>No cracks during electrical and mechanical stress</p> <p>Low hardening temperature and excellent flow properties</p> <p>Fast hardening and good adherence to all cable materials</p> <p>Packed in practical and easy-to-use two-chamber mixing bags</p>
Approvals	<p>Governmental Material Test Laboratory Darmstadt: DIN VDE 0291</p> <p>KEMA, Netherland: Report on the MAK value, which lies well below the maximum value of 0.01 ppm, allowed by law</p>
Storage conditions	<p>Store at optimum temperature of +15°C to +35°C for up to 40 months in original aluminium bag</p>

SPECIFICATIONS:

PART NUMBER	TYPE	VOLUME (ML)
ALC124EG80	EG 80	80
ALC124EG143	EG 143	143
ALC124EG286	EG 286	286
ALC124EG370	EG 370	370
ALC124EG464	EG 464	464
ALC124EG730	EG 730	730
ALC124EG1000	EG 1000	1000
ALC124EG1150	EG 1150	1150
ALC124EG1500	EG 1500	1500
ALC124EG2000	EG 2000	2000



Wattmaster

THE BRAND ELECTRICIANS RELY ON

T: 1300 300 747 **F:** 1300 300 074

www.wattmaster.com.au