

# Alco

## Heatshrink Kit

**PART NO: ALCHSKIT1**

**FEATURES:**

- Environmentally Friendly, Flexible, Flame-retardant, Heat Shrink Tubing
- Complies to UL224
- Dielectric Strength: 15kV/mm
- Operating Temp: -45°C to + 125°C
- Minimum Shrink Temp: 90°C
- Shrink Ratio: 2:1
- RoHS Compliant

**CONTENTS OF KIT:**

PART NUMBER	SIZE (MM)	COLOUR	LENGTH (MM)	QTY
HSTNW2.5/1.25BK	2.5/1.25	Black	50	15
HSTNW2.5/1.25BL	2.5/1.25	Blue	50	15
HSTNW2.5/1.25RD	2.5/1.25	Red	50	15
HSTNW2.5/1.25WH	2.5/1.25	White	50	15
HSTNW2.5/1.25Y	2.5/1.25	Yellow	50	15
HSTNW5.0/2.5BK	5.0/2.5	Black	50	6
HSTNW5.0/2.5BL	5.0/2.5	Blue	50	6
HSTNW5.0/2.5RD	5.0/2.5	Red	50	6
HSTNW5.0/2.5WH	5.0/2.5	White	50	6
HSTNW5.0/2.5Y	5.0/2.5	Yellow	50	6
HSTNW10.0/5.0BK	10.0/5.0	Black	50	10
HSTNW10.0/5.0BL	10.0/5.0	Blue	50	10
HSTNW10.0/5.0RD	10.0/5.0	Red	50	10
HSTNW10.0/5.0WH	10.0/5.0	White	50	10
HSTNW10.0/5.0Y	10.0/5.0	Yellow	50	10
HSTNW13/6.5BK	13/6.5	Black	70	5
HSTNW13/6.5BL	13/6.5	Blue	70	5
HSTNW13/6.5RD	13/6.5	Red	70	5
HSTNW13/6.5WH	13/6.5	White	70	5
HSTNW13/6.5Y	13/6.5	Yellow	70	5
<b>TOTAL QTY</b>				<b>180</b>



**Wattmaster**

THE BRAND ELECTRICIANS RELY ON

**T: 1300 300 747 F: 1300 300 074**

[www.wattmaster.com.au](http://www.wattmaster.com.au)