

Alco

Heatshrink Kit

PART NO: ALCHSKIT2

FEATURES:

- Environmentally Friendly, Flexible, Flame-retardant, Heat Shrink Tubing
- Complies to UL224
- Dielectric Strength: 15kV/mm
- Operating Temp: -45°C to + 125°C
- Minimum Shrink Temp: 90°C
- Shrink Ratio: 2:1
- RoHS Compliant

CONTENTS OF KIT:



PART NUMBER	SIZE (MM)	COLOUR	LENGTH (MM)	QTY
HSTNW2.5/1.25BK	2.5/1.25	Black	50	100
HSTNW5.0/2.5BL	5.0/2.5	Blue	50	50
HSTNW5.0/2.5CL	5.0/2.5	Clear	50	50
HSTNW5.0/2.5RD	5.0/2.5	Red	50	50
HSTNW5.0/2.5Y	5.0/2.5	Yellow	50	50
HSTNW5.0/2.5YG	5.0/2.5	Yellow/Green	50	50
HSTNW5.0/2.5BK	5.0/2.5	Black	50	50
HSTNW7.0/3.55BK	7.0/3.55	Black	50	30
HSTNW7.0/3.55RD	7.0/3.55	Red	50	30
HSTNW7.0/3.55WH	7.0/3.55	White	50	30
HSTNW10.0/5.0BK	10.0/5.0	Black	85	10
HSTNW10.0/5.0CL	10.0/5.0	Clear	85	10
HSTNW13/6.5BK	13/6.5	Black	85	20
HSTNW13/6.5CL	13/6.5	Clear	85	10
HSTNW18/9BL	18/9	Blue	85	5
HSTNW18/9CL	18/9	Clear	85	5
HSTNW18/9RD	18/9	Red	85	5
HSTNW18/9Y	18/9	Yellow	85	5
HSTNW18/9BK	18/9	Black	100	10
HSTNW13/6.5BK	13/6.5	Black	100	10
HSTNW25/12.5BK	25/12.5	Black	250	5
HSMWGL10/3L	10	Black	250	4
HSMWGL25/8L	25	Black	250	4
TOTAL QTY				593

Wattmaster

THE BRAND ELECTRICIANS RELY ON

T: 1300 300 747 **F:** 1300 300 074

www.wattmaster.com.au